

IN THE DRAWINGS:

Attached to the English Translation of the PCT Application are the translated drawings. Also, the PCT page number legends and other PCT markings have been eliminated from all drawing figures. All of those drawing
5 sheets Figs. 1-24 have been marked "Replacement Sheets" and are attached to the English Translation. No new matter is added.

REMARKS

The specification has been amended in accordance with U.S. practice. Also, new claims are presented based on the PCT prosecuted claims but adapted to U.S. practice. Also additional independent claims 35 and 36 have
5 been added.

An Information Disclosure Statement is enclosed.

Respectfully Submitted,



(Reg. 27,841)

10

Schiff, Hardin LLP
CUSTOMER NO. 26574
Patent Department
6600 Sears Tower
233 South Wacker Drive
Chicago, Illinois 60606
Telephone: 312/258-5786
Attorneys for Applicant.

15

SPECIFICATION**TITLE**

5 **" METHOD AND DEVICE FOR CONTROLLING THE CIRCULATION
SPEED OF AN ENDLESS BELT AND ARRANGEMENT FOR GENERATION
OF A BRAKING FORCE ON AN ENDLESS BELT"**

BACKGROUND

10 The invention preferred embodiments concern a method and
a device for controlling the circulation speed of an endless belt, in which an
endless belt is guided over at least two rollers. The belt is driven by a least
one of the rollers with a preset first circulation speed.

15 In electrophotographic printer or copiers, a print image is
electrophotographically generated on a photoconductor, for example an OBC
belt (organic photo [sic] conductor-photoconductor [sic]) in that a charge
image is generated on the photoconductor with the aid of a character
generator and subsequently developed with toner. The toner image is then
transferred onto a belt-shaped intermediate carrier with defined electrical
properties. The intermediate carrier can, for example, be a transfer belt.

20 The toner image located on the intermediate carrier is subsequently
directly transferred onto a carrier material (for example a paper web) at a
transfer printing station, or the toner image located on the intermediate carrier
is re-supplied to the transfer printing region between photoconductor and
intermediate carrier in order to print a further (in particular differently-colored)
toner image over the toner image already located on the intermediate carrier.
25 This method of printing toner images one over the other is also designated as
pick-up of the toner images in a collection mode. The second toner image
can, for example, have a toner color different from that of the first toner image
or contain a special toner, in particular a machine-readable microtoner. A
two-color print with a base color and an additional color can thereby be
30 generated.

 Furthermore, printers and copiers are known in which three or four
different-colored toner images are printed over one another in order to thereby

MARKED-UP COPY

obtain a print image in full-color printing. During the pick-up of the toner images, the intermediate carrier is pivoted away from the carrier material such that no contact between the intermediate carrier and the carrier material is present during the collection. Only when all toner images are printed over one another on the intermediate carrier is a mechanical contact produced between the intermediate carrier and the carrier material in order to transfer the complete, collected toner image onto the carrier material. The mechanical contact is advantageously established at the point in time at which the leading edge of the toner image located on the intermediate carrier has reached the transfer printing location for transfer-printing of the toner image from the intermediate carrier onto the carrier material. A cleaning station is subsequently pivoted onto the carrier element when the point at which the leading edge of the transferred toner image on the intermediate carrier has been located and has reached the cleaning station.

Corresponding stress states (i.e. load states) of the intermediate carrier thereby result due to the different operating phases, due to which stress states the circulation speed of the intermediate carrier is changed. The operating phases and the load states resulting from these are subsequently explained in further detail in the Figure descriptions regarding Figures 1 through 14b.

A slippage occurring dependent on the load state results at the drive roller from the different load states. The circulation speed and the circulation time of the intermediate carrier change due to the different slippage at the drive roller. These changes of the circulation speed or, ~~respectively,~~ circulation time effect a displacement relative to one another of the position of a plurality of successive toner images transferred onto the intermediate carrier as well as the compression of individual toner images or parts of the toner images in the transport direction of the intermediate image carrier.

A print and copier device for performance-adapted monochrome and color one- and two-sided printing of a recording medium is known from the international patent application WO 98/39691 and the US patent 6,246,856. A

MARKED-UP COPY

plurality of different-colored toner images are thereby generated on a photoconductor belt and subsequently transferred onto a transfer belt on which the toner images are collected before they are transferred all together onto a paper web. The collection and transfer occurs in a start-stop operation
5 of the paper web. In the continuous monochrome printing, the toner images are continuously generated in succession on the photoconductor, and transferred onto the transfer belt, ~~[sic]~~ whereby the transfer belt in continuous operation directly further transfers a toner image onto the paper web. The contents of the international patent application WO 98/39691 and of the US
10 patent 6,246,856 are herewith incorporated by reference into the present specification.

Furthermore, in the prior art a plurality of attempts have been made to prevent the position displacement and the length variation of a toner image of the same desired length. It was thus attempted to keep the load change
15 optimally low given the restriction of the transfer belt to a paper web via reduction of the speed difference between paper web and transfer belt. However, depending on the paper properties of the paper web a minimum speed difference is necessary, whereby given a change of the paper type of the paper web to be printed, and in particular of the paper width and the paper
20 thickness, the paper speed, ~~or, respectively,~~ the speed difference between transfer belt and paper web must be readjusted. An arrangement for reduction load ~~[sic]~~ given an activated cleaning unit is known from the German patent document DE 199 42 116 C2. The contents of the patent document DE 199 42 116 C2 as well as the patents ~~or, respectively,~~ patent applications
25 cited therein is herewith incorporated by reference into the present specification. Due to the arrangement known from this document, the forces acting on the transfer belt which are caused by the cleaning unit are reduced. However, a load change that leads to the disadvantages already described remains upon activation of the cleaning unit.

30 In the prior art there were also solution approaches to compensate the print image displacement via an adaptation of the write speed by the imaging

Alternatively, solution proposals are known in which the speed-influenced pivot movements occur before or, ~~respectively,~~ after the toner image generation or, ~~respectively,~~ after the transfer-printing of the toner image onto the carrier material. However, the overall print speed of the ~~printed~~ printer is therewith significantly reduced.

10

15 ~~This object is achieved with the features of the patent claim 1 for a method for controlling the circulation speed of an endless belt. Advantageous developments are specified in the dependent patent claims.~~

20

MARKED-UP COPY

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic design of a printing unit for generation of a one-color toner image on a carrier material;

5 Figure 2 shows the printing unit according to Figure 1, whereby a plurality of toner images are shown that are generated on a photoconductor belt and are already partially transferred onto a transfer belt;

Figure 3 shows the printing unit according to Figures 1 and 2, whereby a part of the generated toner images have already been transfer-printed onto the carrier material;

10 Figure 4 is a printing unit similar to the printing unit according to Figures 1 through 3, whereby two-color print images can be generated with the aid of the printing unit according to Figure 4;

15 Figure 5 shows the printing unit according to Figure 4, whereby (in contrast to Figure 4) print images are generated in a second color after the generation of print images in a first color;

Figure 6 shows the printing unit according to Figures 5 and 6, whereby the print image of a second color is transfer-printed onto the transfer belt over the print image of a first color;

20 Figure 7 shows the printing unit according to Figures 4 through 6, whereby the transfer belt is pivoted onto the carrier material for transfer printing of a two-color toner image;

Figure 8 shows the printing unit according to Figures 4 through 7, whereby the transfer belt has been pivoted onto a cleaning unit after the beginning of the transfer printing of the two-color toner image;

25 Figure 9 shows the printing unit according to Figures 4 through 8, whereby the transfer belt is pivoted away from the carrier material again after the transfer printing of the two-color toner image;

Figure 10 shows the printing unit according to Figures 1 through 3, whereby the printing unit is shown in a first operating phase;

MARKED-UP COPY

Figure 11 shows the printing unit according to Figure 10, whereby the transfer belt is pivoted onto the cleaning unit;

5 Figure 12 shows the printing unit according to Figures 4 through 9, whereby the transfer belt is pivoted onto the paper web as well as onto the cleaning unit in the shown operating phase, and additionally a pressure roller is pivoted onto the paper web at the pressure point;

Figure 13 is a circulation time-time diagram in which circulation times of various operating phases are shown;

10 Figures 14a through 14d show position changes of print images as a consequence of different circulation times;

Figure 15 is an arrangement for braking of the transfer belt according to a first embodiment of the invention;

Figure 16 is an arrangement for braking of the transfer belt according to a second embodiment of the invention;

15 Figure 17 is an arrangement for braking of the transfer belt according to a third embodiment of the invention;

Figure 18 is an arrangement for braking of the transfer belt according to a fourth embodiment of the invention;

20 Figure 19 is an arrangement for braking of the transfer belt according to a fifth embodiment of the invention;

Figure 20 shows force-time diagrams in which are represented the braking forces occurring due to the load states during the operating phases of the printer, the braking forces acting on the transfer belt due to the device for braking and the total braking forces acting on the transfer belt;

25 Figure 21 is an arrangement for controlling the circulation speed of the transfer belt;

Figure 22 is an arrangement for regulating the circulation speed of the transfer belt;

MARKED-UP COPY

Figures 23a through 23e show the change of the circulation speed of the transfer belt give constant drive speed and different braking voltages according to the first embodiment of the invention according to the device according to Figure 15; and

5 Figure 24 shows a circulation time/circulation speed-voltage diagram in which the change of the circulation time and of the circulation speed is shown dependent on the applied voltage.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

10 For the purposes of promoting an understanding of the principles of the invention, reference will now be made to the preferred embodiments illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended, such alterations and further modifications in the illustrated device, and/or method, and such further applications of the
15 principles of the invention as illustrated therein being contemplated as would normally occur now or in the future to one skilled in the art to which the invention relates.

 Via ~~the~~ a method for controlling the circulation speed of an endless belt according to ~~patent claim 1~~, it is achieved that the endless belt can be braked
20 to a second circulation speed, which is in particular advantageous when the belt is braked by the ~~inventive~~ method of the preferred embodiment in a phase with lesser load effect and the belt is not braked or is only slightly braked during operating phases with a load effect of components of the printer or copier on the endless belt.

25 Due to the direct effect of the braking force on the endless belt, inaccuracies and time delays in the generation of a braking effect are prevented.

 A second aspect of the ~~invention~~ preferred embodiment concerns an arrangement for controlling the circulation speed of an endless belt. This
30 arrangement contains an endless belt that is guided over at least two rollers.

MARKED-UP COPY

A drive unit drives the belt over at least one of the rollers with a preset first circulation speed. A braking unit introduces a braking force directly into the belt, via which the belt is braked to a second circulation speed.

5 Via this arrangement it is achieved that the endless belt is simply brought to the second circulation speed via braking.

A third aspect of the invention preferred embodiment concerns an arrangement for generation of a braking force on an endless belt. An electrically-conductive surface is arranged essentially parallel to the endless belt. A voltage relative to the ground potential is provided on the surface for
10 generation of a braking force.

Via this arrangement it is achieved that the braking force directly acts on the endless belt, and thus the belt is braked directly and without temporal delays.

~~For better understanding of the present invention, reference is made to the preferred exemplary embodiments shown in the drawings that are described using specific terminology. However, it is noted that the protective scope of the invention should not thereby be limited since such variations and further modifications to the shown devices and to the method as well as such further applications of the invention as they are shown therein are viewed as~~
15 ~~typical present or future expertise of a competent average man skilled in the art. The Figures show exemplary embodiments of the invention, namely:~~
20

~~Figure 1 — a schematic design of a printing unit for generation of a one-color toner image on a carrier material;~~

~~Figure 2 — the printing unit according to Figure 1, whereby a plurality of toner images are shown that are generated on a photoconductor belt and are already partially transferred onto a transfer belt;~~
25

~~Figure 3 — the printing unit according to Figures 1 and 2, whereby a part of the generated toner images have already been transfer printed onto the carrier material;~~

MARKED-UP COPY

Figure 4 — a printing unit similar to the printing unit according to Figures 1 through 3, whereby two color print images can be generated with the aid of the printing unit according to Figure 4;

5 Figure 5 — the printing unit according to Figure 4, whereby (in contrast to Figure 4) print images are generated in a second color after the generation of print images in a first color;

Figure 6 — the printing unit according to Figures 5 and 6, whereby the print image of a second color is transfer-printed onto the transfer belt over the print image of a first color;

10 Figure 7 — the printing unit according to Figures 4 through 6, whereby the transfer belt is pivoted onto the carrier material for transfer printing of a two-color toner image;

Figure 8 — the printing unit according to Figures 4 through 7, whereby the transfer belt has been pivoted onto a cleaning unit after the
15 beginning of the transfer printing of the two-color toner image;

Figure 9 — the printing unit according to Figures 4 through 8, whereby the transfer belt is pivoted away from the carrier material again after the transfer printing of the two-color toner image;

Figure 10 — the printing unit according to Figures 1 through 3,
20 whereby the printing unit is shown in a first operating phase;

Figure 11 — the printing unit according to Figure 10, whereby the transfer belt is pivoted onto the cleaning unit;

Figure 12 — the printing unit according to Figures 4 through 9, whereby the transfer belt is pivoted onto the paper web as well as onto the
25 cleaning unit in the shown operating phase, and additionally a pressure roller is pivoted onto the paper web at the pressure point;

Figure 13 — a circulation time-time diagram in which circulation times of various operating phases are shown;

Figures 14a through 14d — position changes of print images as a
30 consequence of different circulation times;

Figure 15 — an arrangement for braking of the transfer belt according to a first embodiment of the invention;

MARKED-UP COPY

Figure 16 — an arrangement for braking of the transfer belt according to a second embodiment of the invention;

Figure 17 — an arrangement for braking of the transfer belt according to a third embodiment of the invention;

5 Figure 18 — an arrangement for braking of the transfer belt according to a fourth embodiment of the invention;

Figure 19 — an arrangement for braking of the transfer belt according to a fifth embodiment of the invention;

10 Figure 20 — force time diagrams in which are represented the braking forces occurring due to the load states during the operating phases of the printer, the braking forces acting on the transfer belt due to the device for braking and the total braking forces acting on the transfer belt;

Figure 21 — an arrangement for controlling the circulation speed of the transfer belt;

15 Figure 22 — an arrangement for regulating the circulation speed of the transfer belt;

Figures 23a through 23e the change of the circulation speed of the transfer belt give constant drive speed and different braking voltages according to the first embodiment of the invention according to the device
20 according to Figure 15; and

Figure 24 — a circulation time/circulation speed voltage diagram in which the change of the circulation time and of the circulation speed is shown dependent on the applied voltage.

A printing unit is shown in Figure 1 in which a charge image is
25 generated on a photoconductor belt 22 with the aid of a character generator (not shown), which charge image is subsequently inked with colored toner material (advantageously black toner material) with the aid of a developer unit 28. A toner image is thereby generated on the photoconductor belt 22. The photoconductor belt 22 is guided over deflection rollers 24 and 25 as well as
30 over a drive roller 26. Deflection rods 27a, 27b, 27c for direction of the photoconductor belt 22 are also provided.

MARKED-UP COPY

The drive roller 26 is connected with a drive motor (not shown) and drives the photoconductor belt 22 in the direction of the arrow 23. The printing unit also contains a belt drive for guidance of a transfer belt 17. The belt drive has a drive roller 1 as well as guidance and deflection rollers 1, 5a, 5b, 7, 9, 11, 13, 16. The rollers 5a, 5b and 16 are arranged stationary in the belt drive, whereby the guidance and deflection rollers 7, 9, 11, 13 are connected with one another via a lever arrangement with levers 6, 8, 10, 12, 15 such that a pivot movement of the transfer belt 17 onto a paper web 19 and onto a cleaning unit 21 occurs given a constant belt tension of the transfer belt 17. Two drive units (not shown) are also provided for execution of the pivot movements. The transfer belt 17 is driven in the direction of the arrow 18 with the aid of the drive roller 1 that is connected with a drive unit (not shown).

A load-dependent slippage arises at the drive roller 1 upon driving the transfer belt 17 with the aid of the drive roller 1. The different load states in particular occur via pivoting of the transfer belt 17 onto the paper web 19, the pivoting of the transfer belt 17 onto the cleaning unit 21, the activation of the cleaning corotron 21c and the pivoting of a pressure roller 20 in the transfer printing region between transfer belt 17 and paper web 19.

The rollers 5a and 5b are arranged immediately next to a transfer printing location between the photoconductor belt 22 and the transfer belt 17 and continuously press the transfer belt 17 against the photoconductor belt 22 guided to the transfer printing location by the deflection roller 24.

The printing unit according to Figure 1 is shown in Figure 2, whereby (as described in connection with Figure 1) toner images are generated via inking of the charge images (generated by a character generator) on the photoconductor belt 22 with toner material via the developer unit 28, which charge images are subsequently transferred onto the transfer belt 17. Two toner images 29c, 29d are arranged on the photoconductor belt 22 in Figure 2, whereby a first part of the toner image 29c has already been transfer-printed onto the transfer belt 17 and the developer unit 28 subsequently

MARKED-UP COPY

further inks the latent print image (present as a charge image on the photoconductor belt 22) ~~into~~ ^[sic] on the toner image 29d. The toner images 29b and 29a inked beforehand by the developer unit 28 have already been transferred onto the transfer belt 17 and are transported in the direction of the arrow 18 with the transfer belt 17 on its surface up to a transfer printing location at which they are then transferred from the transfer belt 17 onto the paper web 19. In the operating phase shown in Figure 2, the transfer belt 17 is pivoted onto a cleaning unit 21 such that the cleaning unit 21 is activated. The pivoting occurs with the aid of a drive unit (not shown) for movement of the lever 8, whereby the levers 6 and 10 are also moved. The transfer belt 17 is pivoted onto the cleaning unit 21 via this lever movement. The belt tension of the transfer belt 17 always remains constant given the pivot movement of the levers 6, 8, 10. The levers 6, 8, 10 participating in the pivot movement are shown hatched in Figure 2.

The printing unit according to Figure 1 and 2 is shown in Figure 3, whereby the transfer belt 17 is pivoted both onto the paper web 19 and onto the cleaning unit 21 such that the toner images 29b through 29f located on the transfer belt 17 are transferred onto the paper web 19. The paper web 19 is accelerated to transport speed just before the pivoting of the transfer belt 17 and moved in the direction of the arrow 30. The pivot levers 6, 8, 10, 12 and 15 are thereby directed with the aid of drive units such that the transfer belt 17 contacts the paper web 19 in a transfer printing region between the rollers 11 and 20, whereby the pressure roller 20 is pivoted from below onto the paper web 19 simultaneously with the pivoting of the transfer belt 17 onto the paper web 19. The levers 6, 8, 10, 12, 15 participating in the pivot movements are shown with a hatched fill in Figure 3.

The pivot lever mechanism is moved with the aid of a second drive unit such that the transfer belt 17 is in particular pivoted onto the cleaning unit 21 via the direction of the roller 9, after which at least one part of the first generated toner image 29h has been transfer-printed onto the paper web 19 and at least the point of the transfer belt 17 at which the leading edge of the

MARKED-UP COPY

toner image 29h was located arrives in the cleaning region of the cleaning unit 21. The cleaning unit 21 contains a discharge corotron 21c via whose high voltage corotron [sic] the toner residues located on the transfer belt are discharged.

5 The cleaning unit 21 also contains a brush 21b that brushes the toner residues located on the transfer belt 17 off from this, whereby the rotation direction of the cleaning brush 21b is provided counter to the transport direction of the transfer belt 17, such that a large brush effect (and thus an efficient cleaning effect) is achieved. With the aid of a suitable device, the
10 toner material removed with the aid of the brush 21b is separated from this and re-supplied to the developer unit 28. Alternatively, the brush 21b can also [sic] move in the opposite direction, for example with a circumferential speed different from the circulation speed of the transfer belt 17. The removed toner material can alternatively be supplied to a residual toner reservoir.

15 Toner images 29a, 29b, 29c, 29d, 29e, 29f, 29g, 29h~~are~~ [sic] are shown in Figure 3 that have been successively inked with the aid of the developer unit 28, whereby toner image 29a was inked first and the toner image 29h was inked last. The toner image 29h has not yet been completely generated and is subsequently further completed via inking of a charge image
20 present on the photoconductor belt 22. As already described, the toner images 29a through 29h are successively inked on the photoconductor belt 22 with the aid of the developer unit 29, subsequently transferred from this photoconductor belt 22 onto the transfer belt 17 and subsequently transferred onto the paper web 19. The generation of the toner images 29a through 29h
25 ensues occurs continuously, whereby the photosensitive belt 22, the transfer belt 17 and the paper web 19 are driven with essentially the same speed after the pivoting of the transfer belt 17 onto the paper web 19. To tighten the paper web 19, the drive speed of the transfer belt 17 is slightly higher than the drive speed of the paper web 19. The transfer belt 17 is thereby essentially
30 braked to the drive speed of the paper web 19 after the pivoting onto the paper web 19. The pivoting of the paper web 19 thus effects a speed

MARKED-UP COPY

difference of the circulation speed of the transfer belt 17 due to the lower drive speed of the paper web. A greater slippage at the drive roller 1 of the transfer belt drive is generated by the braking of the transfer belt 17 upon contact with the paper web 19 and the contact pressure of the pressure roller 20.

5 A printing unit of Fig. 4 is similar to the printing unit according to Figures 1 through 3, whereby a two-color toner image can be generated on the paper web 19 ~~with the aid of the printing unit according to Figure 4~~. Identical elements have identical reference characters. In Figure 4, four toner images 29a through 29d have been generated with the aid of the developer
10 unit 28, whereby the toner images are inked with black toner material. Upon inking with toner material of the charge images generated via the character generator, the developer unit 28 is activated and a developer unit 31 for development of toner images with red toner material is deactivated. In the operating phase shown in Figure 4, the transfer belt 17 is pivoted away from
15 the paper web 19 and onto the cleaning unit 21.

 The printing unit according to Figure 4 is shown in Figure 5, whereby the toner image 29d has been entirely generated with the aid of the developer unit 28 and has almost completely been transferred from the photoconductor belt 22 onto the transfer belt 17. A further toner image 32a has subsequently
20 been generated on the photoconductor belt 22 with the aid of the activated developer unit 31 given a deactivated developer unit 28, whereby the character generator has previously generated a corresponding charge image on the photoconductor belt 22. In the operating state shown in Figure 5, only a first part of the entire toner image 32a is inked with red toner material by the
25 developer unit 31. The further print image of the toner image 32a is already located on the photoconductor belt 22 as a charge image and is thus present as a latent print image that is subsequently inked with red toner material with the aid of the developer unit 31.

 The printing unit according to Figures 4 and 5 is shown in Figure 6,
30 whereby the toner image 32a is transfer-printed on the toner image 29a that is located on the transfer belt 17 and has been re-supplied to the transfer

MARKED-UP COPY

printing location between the photoconductor belt 22 and the transfer belt 17. The leading edge of the toner image 29a coincides with the leading edge of the toner image 32a such that the toner images 29a and 32a are essentially congruent. In the operating state shown in Figure 6, a further toner image
5 32b has been generated with the aid of the developer unit 31, whereby the separation between the toner images 32a and 32b essentially corresponds to the separations of the toner images 29a and 29b; 29b and 29c; 29c and 29d. The printing unit according to Figure 6 thus has generated a second red toner image 32a on the black toner image 29a.

10 The printing unit according to Figures 4 through 6 is shown in Figure 7, whereby after the pivoting of the transfer belt 17 onto the paper web 19 with the aid of the levers 10, 12 and 15, a first part of the toner images 29a and 32a printed over one another have been transferred onto ~~said~~ the paper web 19. The pressure roller 20 is pivoted onto the paper web 19 from below
15 simultaneously with the pivoting of the transfer belt 17 onto the paper web 19. The paper web 19 has been accelerated to transport speed before both pivoting processes, as is described in connection with Figures 1 through 3 for the printing unit shown there.

Further toner images 32a, 32c, 32d were generated in a red toner color
20 with the aid of the developer unit 31 and are essentially congruent in the outer dimensions with the toner images previously inked black with the aid of the developer unit 28. The toner image ~~32d~~ 32a is superimposed on the toner image ~~29d~~ 29a, the toner image 32c is superimposed on the toner image 29c and the toner image 32d is superimposed on the toner image 29d-~~[sic]~~. This
25 superimposition of the toner images is also designated as pick-up. The generation of the toner images placed atop one another thus occurs in a collection mode. In the operating state shown in Figure 7, the transfer belt 17 is not yet pivoted onto the cleaning unit 21 since the point at which the leading edge of the toner images 29a and 32a has been located has not yet reached
30 the cleaning region in the cleaning unit 21.

MARKED-UP COPY

In Figure 7, a further toner image 33a has been generated with black toner material on the photoconductor belt 22 with the aid of the developer unit 28.

5 The printing unit ~~[[is]]~~ shown according to Figures 4 through 7 is shown in Figure 8, whereby a further part of the toner images 29a and 32a has been transferred onto the paper web 19. The point at which the leading edge of the toner images 29a and 32a has been located has reached the cleaning region of the cleaning unit 21, whereby the pivot levers 6, 8 and 10 are moved (at the latest upon arrival at this point of the transfer belt 17 in the cleaning region of
10 the cleaning unit 21) with the aid of a drive unit (not shown) such that the transfer belt 17 is pivoted onto the cleaning unit 21, whereby the positions of the pivot levers 12 and 15 are not altered upon pivoting of the transfer belt 17 onto the cleaning unit 21. The belt tension of the transfer belt 17 is also not changed both upon pivoting of the transfer belt 17 onto the paper web 19 and
15 upon pivoting of the transfer belt 17 onto the cleaning unit 21.

A printer for performance-adapted monochrome and color one- and two-sided printing of a recording medium is known from WO 98/39691 and the US patent 6,246,856, whereby the pivoting of the transfer belt onto and off of the recording medium is described in detail in this patent application or,
20 ~~respectively,~~ in this patent. The content of the patent application WO 98/39691 and the content of the US patent 6,246,856 is ~~is-~~~~[sic]~~ are herewith incorporated by reference into the present specification.

The printing unit according to Figures 4 through 8 is shown in Figure 9, whereby the entire toner images shown collected (i.e. printed over one
25 another) in Figure 8 have been transferred to the paper web 19. The trailing edge of the print images 29d/32d were transferred last onto the paper web 19. After the trailing edges of these toner images 29d/32d have been transferred onto the paper web 19, the transfer belt 17 has been pivoted away from the paper web 19 with the aid of the drive device (not shown) via movement of the
30 levers 10, 12 and 15. Furthermore, both the discharge corotron 21c and the cleaning brush 21b are activated, whereby the transfer belt 17 is furthermore

MARKED-UP COPY

pivoted onto the cleaning unit 21. The cleaning brush 21b[,] and the cleaning corotron 21c remain activated at least until the point on the transfer belt 17 at which the trailing edges of the toner images 29d/32d ~~have been~~ located on the transfer belt 17 has completely passed through the cleaning region of the cleaning unit 21. The toner image 22a already generated in the operating mode or status ~~[sic] or, respectively,~~ operating state already shown in Figure 8 ~~has been at~~ is at least partially transferred from the photoconductor belt 21 onto the transfer belt 17. A further toner image 33b is generated on the photoconductor belt 22 with the aid of the developer unit 28.

Both the toner image 22a and the toner image 33b have been inked with the toner material in the color black.

The printing unit according to Figures 1 through 3 is shown in Figure 10, whereby in contrast to the operating states shown in Figures 1 through 3 the printing unit is shown in an operating state in which print images 29a through 29d are transported on the photoconductor belt 22 and the transfer belt 17, whereby the transfer belt 17 is pivoted away from the cleaning unit 21 and the paper web 19. A load state of the transfer belt 17 similar to the load state according to Figure 1 is thus shown in Figure 10, whereby in contrast to the load state according to Figure 1 toner images 29a through 29d are generated ~~or, respectively,~~ transported. No braking effect is thereby exerted on the transfer belt 17 due to the contact of the transfer belt 17 with the cleaning unit 21 and no braking effect is exerted on the transfer belt 17 due to the contact of the transfer belt 17 with the paper web 19. The toner images 29a, 29b and 29c transferred from the photoconductor belt 22 onto the transfer belt 17 have thus been transferred at a higher first circulation speed v_1 of the transfer belt 17 according to Figure 10. Given the load state according to Figure 2[,] in which the transfer belt 17 is pivoted onto the cleaning unit 21, at least the toner image 29c is transferred from photoconductor belt 22 onto the transfer belt 17 at a second middle circulation speed v_2 of the transfer belt 17. Given a transfer belt 17 pivoted onto the paper web 19 and onto the cleaning unit 21, at least the toner image 29c in

MARKED-UP COPY

Figure 3 ~~at least this toner image 29c [sic]~~ is transferred onto the transfer belt 17 at a third low circulation speed v_3 of the transfer belt 17.

The circulation speed of the photoconductor belt 22 is thereby constant, independent of the circulation speed of the transfer belt 17. The
5 toner images are thereby not transferred and compressed at the first circulation speed v_1 of the transfer belt 17 at the transfer printing location between photoconductor belt 22 and transfer belt 17, meaning that the length of the toner images on the photoconductor belt 22 corresponds to the subsequent length of the same toner images on the transfer belt 17. If the
10 toner images are transferred from the photoconductor belt 22 onto the transfer belt 17 at middle circulation speed v_2 , the toner image is compressed by a first amount upon transfer and is compressed by a second amount upon transfer of a toner image at the third, lower circulation speed v_3 of the transfer belt 17.

The toner images are thereby compressed in a range between a
15 thousandth and multiple millimeters. This affects the length of the subsequent print image generated on the paper web 19 as well as its position on the paper web 19. Given the load state according to Figure 10, the circulation of the transfer printing 17 occurs with a first high circulation speed v_1 that is additionally designated in Figure 10 with the reference character 34. The
20 speed v of the photoconductor belt 22 is also additionally designated with the reference character 35.

The printing unit according to Figure 10 is shown in Figure 11, whereby the print images 29a through 29d have been generated in the same manner as in Figure 10, whereby, however, the transfer belt 17 is pivoted onto the
25 cleaning unit 21 with the aid of the levers 6, 8 and 10 at least upon transfer of the toner image 29c from the photoconductor belt onto the transfer belt 17. Due to the pivoted cleaning unit 21 ~~[sic]~~, the circulation of the transfer belt 17 occurs with the second, middle circulation speed v_2 , whereby in Figure 11 the middle circulation speed v_2 is ~~with [sic]~~ additionally designated with the
30 reference character 33.

MARKED-UP COPY

The printing unit according to Figures 4 through 9 is shown in Figure 12, whereby the transfer belt 17 is pivoted both onto the cleaning unit 21 and onto the paper web 19. The pressure roller 20 is also pivoted onto the paper web 19 from below. The circulation of the transfer belt 17 thereby occurs with
5 a lower third circulation speed v_3 that is additionally designated with the reference character 35 in Figure 12.

A circulation time-time diagram 40 is shown in Figure 13 as a screen printout of an evaluation software for evaluation of measurement values determined with the aid of a [sic] unit on the printing unit according to one of
10 the printing units shown in Figures 1 through 12. The current time is thereby plotted on the abscissa and the circulation time of a belt circulation of the transfer belt 17 is plotted on the ordinate. In the diagram 40, the circulation speeds v_1 , v_2 and v_3 of the transfer belt 17 during the operating states shown in Figures 10 through 12 have been determined. During the operating states
15 41a and 41b, the transfer belt 17 has neither mechanical contact with the cleaning unit 21 nor mechanical contact with the paper web 19. In these operating states, the transfer belt 17 has a circulation time of 1788.51 ms, which corresponds to the circulation speed v_1 . During the operating state 42, the transfer belt 17 has mechanical contact with the activated cleaning unit
20 21, however no mechanical contact with the paper web 19. During the operating state 42, the transfer belt 17 has a circulation time of 1788.58 ms, which corresponds to a speed v_2 .

During the operating state 43, the transfer belt 17 has both mechanical contact with the cleaning unit 21 and mechanical contact with the paper web
25 19. During the operating state 43, the transfer belt 17 has a circulation speed of 1788.67 ms and thus a speed v_3 . The circulation speed of the transfer belt 17 thereby varies between the speeds v_1 through v_3 . The circulation speed of the photoconductor belt 22 always remains constant during the operating phases 41a, 41b, 42 and 43. The circulation time of the transfer belt 17
30 results from the quotient of the length of the transfer belt 17 and the circulation speed of the transfer belt 17.

MARKED-UP COPY

In the printing units according to Figures 1 through 12, the relative speed deviation is less than $2/1000$ of the nominal circulation speed. However, in practice (in particular in two-color and multi-color printing) it has visible effects. With the aid of the printing units according to Figures 1
5 through 12, one page or multiple pages with a total length of up to 1650 mm can be generated in an exemplary design embodiment of these printing units. After the load-conditional reduction of the circulation speed of the transfer belt 17 by (relatively) $1/1000$ of the circulation speed after the transfer printing of a first toner image and before the transfer printing of a second toner image, the
10 second toner image transferred from the photoconductor belt 22 onto the transfer belt 17 is compressed by 1% ~~[sic]~~ relative to the first toner image during this transfer such that, given a congruent start of the page by both toner images, the page end of the second toner image ends earlier than the page end of the first toner image.

15 Given a write length of the first color separation of 1650 mm, i.e. given a toner image with a length of 1650 mm in a first toner color, and given a compression of the subsequent printing of a second toner image in a second color on this first toner image, the second toner image is shorter by 1.65 mm than the first toner image (1% of 1650 mm write length of the first circulation).

20 A second ~~second~~ ~~[sic]~~ toner image transferred at a higher circulation speed (in comparison to a first circulation speed) is expanded in the same manner in relation to the first toner image. The relative speed difference results from the quotients of the speed v_{x1} at which the first toner image is transferred and the speed v_{x2} at which the second toner image is transferred,
25 whereby the amount 1 is subtracted from this quotient. The absolute length error dl results from the multiplication of the write length possible on the transfer belt 17 and the relative speed difference.

The product from $1650 \text{ mm} \times 0.01 = 1.65 \text{ mm}$ thus results in the present example for calculation of the length error, whereby a positive
30 algebraic sign of the length error results given a speed increase and a negative algebraic sign of the length error results given a speed reduction.

MARKED-UP COPY

The human eye very clearly detects a line offset given a plurality of print images of different colors printed over one another and feels this to be disturbing, whereby this offset is generally designated as color fringe in printing technology. 2/100 mm offset is thereby already clearly detectable and
5 is sensed as disturbing. It results from this that, given a possible length of a print image printed over one another [sic] of 1650 mm, the speed change may maximally amount to 0.012 %, whereby this value is calculated as follows:

Allowable speed change

$$= \frac{0.020 \text{ mm}}{1650 \text{ mm} \times 1000 \%} = 0.012 \%$$

10

The effects of the compression of the print images at the transfer printing location between photoconductor belt 22 and transfer belt 17 are shown in Figures 14a through 14d using schematically shown print sides 48a through 48d. Five print images of print sides that are successively generated
15 and transferred onto the transfer belt 17 are shown in Figure 14a, which print sides are subsequently transfer-printed onto an endless paper web 45. In contrast to this, the second color printout that is designated with 48b in Figure 14v was transferred onto the transfer belt 17 with a circulation speed v_2 of the transfer belt 17 after the pivoting of the cleaning unit 21, whereby the print
20 sides shown in Figure 14b should at least correspond in the outer contours to the print sides according to Figure 14a. However, the length of the print sides is different due to the different circulation speed v_1 , v_2 of the transfer belt 17, i.e. due to the difference of the speeds v_1 and v_2 . The second toner image according to Figure 14b is also generated in second toner color differing from
25 the toner image according to Figure 14a. The transfer belt 17 has an even lower circulation speed v_3 after the pivoting of the transfer belt 17 onto the paper web 19, 45.

The transfer belt 17 is subsequently pivoted away from both the paper web 19 and the cleaning unit 21, such that the transfer belt 17 again has a
30 circulation speed v_1 . The subsequently generated print images are then again transferred uncompressed from the photoconductor belt 22 onto the transfer

MARKED-UP COPY

belt 17. The change of the total length of the five successively-generated print sides of 1650 mm given a change of the circulation speed of the transfer belt 17 from the circulation speed v_1 to the circulation speed v_2 is designated by the arrow 49a; the offset given a change of the circulation speed v_1 to the circulation speed v_3 is designated with the arrow 49b; and the offset given the change of the circulation speed v_3 to the circulation speed v_1 is designated with the arrow 49c.

The physical length of one page on the paper web 45 is specified with the aid of the dimensioning, the physical length of the toner image transferred onto the transfer belt 17 (which toner image is transferred onto the paper web 17 after the collection of the toner images on the transfer belt 17) is respectively specified with the dimensions 47a through 47d. In Figures 14a through 14d, the physical page lengths are respectively specified by perpendicular dashed lines.

The offset of the toner images generated or, ~~respectively,~~ transfer-printed at the circulation speed v_1 in relation to the toner images generated or, ~~respectively,~~ transfer-printed at the speed v_2 is clarified by the dash-dot lines indicated between the print images of Figure ~~[sic]~~ 14a and 14b, whereby the offset between the individual print images is clarified via the increasing slope of the initially horizontal dash-dot line in successive print image starts and ends. In Figure 14b it is likewise visible that the third print image is already transfer-printed onto the paper web 45 before the physical page border, whereby a part of the toner image of this print page is truncated in a subsequently cutting process. Larger parts of the print page are then truncated in the subsequently printed fourth and fifth print pages, whereby parts of the subsequent print page are respectively contained on the preceding print page according to the layout.

In the ~~inventive~~ solution of the preferred embodiment to the problem, the individual influences that lead to a speed reduction of the transfer belt 17 from the circulation speed v_1 to the circulation speed v_3 are not prevented by elaborate measures such as in the prior art; rather, the transfer belt 17 is

MARKED-UP COPY

braked to the speed v_3 even given load states with higher circulation speeds v_1 and v_2 , or is braked to a speed lower than the speed v_3 during all load states.

5 Devices to reduce the circulation speed of the transfer belt 17 are subsequently specified in Figures 15 through 22. These devices thereby form the basis of the realization that conductive surfaces connected to a voltage source, to which conductive surfaces a belt-shaped material (in particular an endless belt) is directed, exert a braking force in this belt ~~on the belt [sic]~~ due to the generated electrostatics and thus effect a braking effect on the belt. In 10 the devices according to Figures 15 through 22, this perception is used for realization of a braking arrangement via which the circulation speed of the transfer belt 17 is reduced. The braking force of the braking arrangement is thereby advantageously changed dependent on the load states, such that a constant circulation speed of the transfer belt 17 is generated given all load 15 states.

Printing units similar to the printing units according to Figures 1 through 12 are shown in Figures 15 through 19 as well as 21 and 22. Identical elements have the same reference characters. A metal plate rounded at the edges is arranged on the inner side of the transfer belt 17, over which metal 20 plate the transfer belt 17 is directed upon actuation of the transfer belt 17 with the aid of the drive roller 1. The metal plate 55 is supplied with a high voltage (adjustable relative to the ground potential of the printer) with the aid of a high voltage source 56 with adjustable voltage. Due to the high voltage, a braking force 58 is generated in the transfer belt 17 that directly acts on the transfer 25 belt 17, whereby the transfer belt 17 is braked.

A diagram 57 is also shown in Figure 15 in which is shown a graph of the voltage curve of the high voltage (represented with the aid of a point line) and, with a graph shown with a solid line, the braking force (generated by the high voltage) with which the transfer belt 17 is braked. The time curve of the 30 high voltage is controlled dependent on the different load states already described, such that an essentially constant circulation speed of the transfer

MARKED-UP COPY

belt 17 is effected. In Figure 15, the transfer belt 17 is pivoted away from both the paper web 19 and the cleaning unit 21 such that the transfer belt 17 is braked with maximum required braking force to a constant low circulation speed v_4 .

5 In contrast to Figure 15, in Figure 16 a high voltage source with constant high voltage is provided, whereby the high voltage source 60 according to Figure 16 supplies the high voltage to the metal plate in the form of voltage pulses of different pulse breadth or, ~~respectively,~~ pulse width. If a greater braking force is required, the pulse widths are increased and the
10 pauses between the individual pulses are reduced. Conversely, if a smaller braking effect is required, the pulse width of the individual pulses is reduced and the pauses between the pulses are increased. This dependency of the braking force on the pulse width is also shown in diagram 61, whereby the voltage pulses are represented by hatched surfaces and the braking force
15 resulting from this are ~~[sic]~~ represented with the aid of a graph shown with a solid line.

 In contrast to Figures 15 and 17, no metal plate 55 is provided in the printing unit shown in Figure 17; rather a plurality of strip-shaped metal plates 65a through 65d arranged next to one another and insulated from one another
20 are arranged in the transport direction of the transfer belt 17, to which metal plates 65a through 65d is alternately supplied a constant high voltage (generated by a high voltage source 67), ~~respectively~~ via a switch 66a through 66d. The surface charged with the high voltage is thereby simply changed with the aid of the switch 66a through 66d, whereby the braking force is
25 dependent on the effective surface charged with high voltage. The dependency of the braking force on the effective surface is likewise represented in the force-time diagram 68, whereby the metal plate 65a forms the areal segment A1, the metal plate 65b forms the areal segment A2, the metal plate 65c forms the areal segment A3 and the metal plate 65d forms the
30 areal segment A4. The total braking force acting on the transfer belt 17 then changes dependent on the area of the individual elements, as shown in the

MARKED-UP COPY

diagram 68. The areal segments charged with high voltage are specified with the aid of the footnotes [sic] of the areal segments. Given the areal segment A₃₄, the metal plates 65c and 65d are thus charged with high voltage via closing of the switches 66c and 66d.

5 The arrangement for braking the transfer belt 17 shown in Figure 18 is similar to the arrangement according to Figure 17, whereby given a state in which [sic] no high voltage of the high voltage source 67 is supplied to the metal plates 65a through 65d, but rather ground potential is supplied via a circuit arrangement. Floating potentials of these metal plates 65a through 65d
10 are thereby prevented. The braking effect of this arrangement essentially coincides with the braking effect of the arrangement according to Figure 17, as is also shown in diagram 68.

 An arrangement for generation of a braking force that acts directly on the transfer belt 17 is shown in Figure 19. The arrangement of the metal
15 plates 65a through 65d essentially coincides with the arrangement according to Figures 17 and 18. A first high voltage generated by a high voltage source 67 or a second high voltage generated by a high voltage source 71 can selectively be supplied to the individual metal plates 65a through 65d via the switches 66a through 66d (which are realized as change-over switches). A
20 potential difference differing from the ground potential can thereby be generated between the individual metal plates 65a through 65d, whereby in particular one of the high voltage sources 67 and 71 can ~~generated~~ generate a high voltage negative relative to the ground potential. A braking force is generated via feeding the high voltage source [sic] 67 to the individual metal
25 plates 65a through 65d in the same manner as in Figures 17 and 18, whereby the surface-dependent braking force is shown in the diagram 68 that essentially coincides with the diagrams 68 according to Figures 17 and 18.

 Three diagrams 75, 76 and 77 are shown in Figure 20, whereby the braking forces active due to the different load states on the transfer belt 17
30 are shown in the diagram 75 and the braking force generated by one of the braking ~~device~~ [sic] according to Figures 15 through 19 is shown dependent on the time in the diagram 76. A diagram 77 is also shown in Figure 17, in

MARKED-UP COPY

which the sum of the braking forces from the diagrams 75 and 76 is shown, whereby a constant resulting braking force 78 is generated by the braking arrangement controlled dependent on load. In the diagram 75, the braking force generated by the cleaning unit 21 is designated with F_{Cle} , the braking
5 force resulting due to the pivoting of the transfer belt 17 onto the paper web 19 is designated with F_{Paper} , the braking force generated given a pivoted transfer belt 17 on the paper web 19 and simultaneous pivoting of the transfer belt 17 onto the cleaning unit 21 is designated with $F_{Cle+Pap}$. The resulting braking force 78 can thus be held constant over the entire time span (i.e.
10 during the various operating phases with the different load states) due to the shown braking arrangements, whereby the transfer belt 17 has a constant circulation speed. The different lengths of the toner images are thus effectively prevented. Toner images with an exact preset length are generated. Exactly congruent toner images are even generated given multi-
15 color printing, whereby a color image fringe is prevented.

A braking arrangement according to Figures 15 and 16 is shown in Figure 21, whereby (in contrast to Figures 15 and 16) the metal plate 55 is supplied with a high voltage generated at a high voltage source 80. The high voltage source 80 can output an adjustable variable high voltage, whereby the
20 level of the output high voltage can be adjusted with the aid of a microprocessor 81 connected with a control input of the high voltage source 80.

The microprocessor 81 furthermore controls drive motors 83a and 83b for execution of the pivot movements of the transfer belt 17 onto the cleaning
25 unit 21 and onto the paper web 19 with the aid of the lever mechanism of the levers 6, 8, 10, 12, 15. The outputs of the microprocessor 81 for activation of the drive motors 83a and 83b are connected with power converters 82a, 82b that convert the control signals of the microprocessor 81 into motor activation signals for activation of the motors 83a and 83b; whereby the motors 83a and
30 83b are advantageously step motors. The motor 83a thereby executes a pivot movement of the lever 6 and the motor 83b executes a pivot movement

MARKED-UP COPY

of the lever 10. The same microprocessor 81 thereby controls high voltage generating the braking effect and the pivot movement of the transfer belt 17. The load changes generated by the pivot movements can thus very simply be taken into account in the determination of the high voltage to be set and the
5 braking force resulting from this, whereby a corresponding change of the braking force effected by the metal plate 55 ~~[sic]~~ is be generated at the same point in time at which a load change occurs (or, in the event that it is necessary, before this point in time) in order to ensure the constant braking force 78 shown in Figure 20.

10 The braking arrangement according to Figure 21 is shown in Figure 22, whereby the high voltage source 80 is activated by a microprocessor 84 to which a desired value 86 of the circulation speed of the transfer belt 17 is supplied and to which a real value of the circulation speed is supplied with the aid of a sensor 85 to detect the circulation speed of the transfer belt 17. As
15 an alternative to the velocity sensor 85, the circulation time of the transfer belt 17 can also be detected with the aid of a suitable sensor arrangement from which the circulation speed is then simply determined with the aid of the belt length of the endless belt. The microprocessor 84 implements a real value-desired value comparison and, dependent on the control deviation, generates
20 a control signal that supplies the high voltage source 80 ~~[sic]~~ to the microprocessor 84. The high voltage source 80 thus serves as a control element of the control loop.

The circulation times of the transfer belt 17 are respectively shown in Figures 23a through 23e dependent on the set direct voltage. The effective
25 surface of the metal plate 55 is thereby 545 cm², whereby the circulation speed v_1 is only 992 mm/s at a high voltage of 0 kV. The average circulation time is respectively shown in Figures 23a through 23e with the aid of a dash-dot line. As already mentioned, in Figure 23a no high voltage is applied to the metal plate 55; rather, ground potential or, ~~respectively,~~ a potential
30 corresponding to ground potential is applied. The average belt circulation time is 1790.94 ms. A diagram is shown in Figure 23b in which the circulation

MARKED-UP COPY

time of the transfer belt 17 occurs given a charging of the metal plate 55 with a high voltage of 0.4 kV. The average circulation time of the transfer belt 17 is thereby likewise 1790.94 ms.

5 The circulation time of the transfer belt 17 is shown in Figure 23c given a charging of the metal plate 55 with a high voltage of 0.80 kV. The circulation time of the transfer belt 17 is thereby on average 1791.09 ms. The circulation time of the transfer belt 17 given a charging of the metal plate 55 with a voltage of 1.2 kV is shown in Figure 23d. The average circulation time is thereby 1791.21 ms. Given a charging of the metal plate 55 with a voltage
10 of 1.6 kV, the average circulation time of the transfer belt 17 is 1791.35 ms, as shown in Figure 23e.

A circulation time/circulation speed-voltage diagram is shown in Figure 24, in which the change of the absolute circulation time and the change in the circulation time is represented dependent on the change of the supplied
15 voltage. The graph represented with the aid of a dashed line thereby specifies the variation of the absolute circulation time, and the graph represented with the aid of a solid line specifies the change of the circulation time with increasing voltage. The metal plate 55 or, ~~respectively,~~ the metal plates 65a through 65d ~~is~~ ~~[sic]~~ are arranged on the inner side of the transfer
20 belt 17 in the exemplary embodiments.

The braking effect on the transfer belt 17 may be based on the fact that an electrical field through which the transfer belt 17 is directed is generated between the metal plate 55 or, ~~respectively,~~ the metal plates 65a through 65d and the components of the printer that have a potential differing from the
25 potential of the metal plate 55, 65a through 65d. The metal plate 55, 65a through 65d is thus a capacitor plate. The electrical field effects a temporary displacement of charges in the transfer belt 17. Due to the displacement, a concentration of charges opposite the charge of the capacitor plate occurs in the transfer belt 17 towards the metal plate 55, 65a through 65d. The charges
30 in the transfer belt 17 are thereby attracted by the charge of the capacitor plate 55, 65a through 65d with a force according to Coulomb's Law. Due to

MARKED-UP COPY

this force, the transfer belt 17 is drawn in the direction of or against the metal plate 55, 65a through 65d (i.e. capacitor plate), whereby, given a contact between the metal plate 55, 65a through 65d and the transfer belt 17, depending on the size of this attractive force a friction force is generated
5 between metal plate 55, 65a through 65d and transfer belt 17 that reduces the transport speed. A braking force independent of the rollers of the belt drive is thereby generated that acts directly on the transfer belt 17. A further metal plate can also be arranged on the side of the transfer belt 17 opposite the metal plate 55, 65a through 65d, essentially in parallel with the metal plate 55,
10 65a through 65d, at a preset distance from the transfer belt. To generate the braking force, the further metal plate then has a potential (advantageously ground potential) differing from the potential of the metal plate 55, 65a through 65d.

In other exemplary embodiments, the metal plate 55, 65a through 65d
15 can also be arranged on the outer side of the transfer belt 17 at a distance from the transfer belt 17, such that a toner image located on the transfer belt 17 is not damaged by the metal plates 55, 65a through 65d. As an alternative to a direct voltage, the high voltage sources 56, 60, 67, 71 can also ~~generated~~
generate an alternating voltage with which the plates 55, 65a through 65d are
20 charged. The braking force generated via the feed of the high voltage acts directly and without temporal delay on the transfer belt 17. A very exact and time-precise control of the braking force is thereby possible. The metal plates 65a through 65d, 55 advantageously extend over the entire width of the transfer belt 17. Due to the inventive braking arrangements, the transfer belt
25 17 and the plates 55, 65a through 65d are subject to only very ~~sight~~ slight wear.

As an alternative to the shown embodiments, the surface generating the braking force can also be divided up into segments transverse to the transfer belt 17 that can be charged individually or in groups with high voltage
30 of the same voltage level or different voltage levels. The metal plates 55, 65a through 65d ~~can simply [sic] metal plates [sic], in particular~~ are metal plates

MARKED-UP COPY

that contain a stainless steel alloy, copper or a copper alloy or that contain an aluminum alloy or aluminum. The plates can also be subjected to a surface treatment or be provided with a coating. Alternatively, electrically-conductive plastics can also be used as a plate 55. The plates {sic} 55 are
5 advantageously provided with a smooth surface or with a suitable surface structure. Further variations of the regulation (for example the detection of the real value of the circulation speed with the aid of the circulation time) of a desired value specification controlled by a further process are possible in order to realize inventive applications. The ~~inventive~~ braking arrangement of
10 the preferred embodiment was provided in the shown exemplary embodiments for braking of the transfer belt 17. However, such a braking arrangement for braking of the photoconductor belt 22 or further belt-shaped carrier material is also possible, whereby the endless carrier material does not necessarily have to be an endless, circulating belt. Rather, the belt 17 to be
15 braked can also be a paper web or single sheets with a relatively large length.

Although a preferred exemplary ~~embodiments of the invention have~~ embodiment with various modifications been shown and described in detail in the drawings and in the preceding specification, ~~they~~ it should be viewed as purely exemplary and not as limiting the invention. It is noted that only the
20 preferred exemplary ~~embodiments are~~ embodiment is shown and described, and all variations and modifications that presently and in the future lie within the protective scope of the invention should be protected.

MARKED-UP COPY

~~Reference characters~~

- ~~1, 26—drive roller~~
- ~~5a, 5b, 7, 9,~~
- ~~11, 13, 16, 24, 25—deflection roller~~
- 5 ~~27a, 27b, 27c—deflection rod~~
- ~~6, 8, 10, 12, 15—pivot lever~~
- ~~17—transfer belt~~
- ~~18, 23, 30—direction arrows~~
- ~~19—paper web~~
- 10 ~~20—pressure roller~~
- ~~21—cleaning unit~~
- ~~21b—cleaning brush~~
- ~~21c—cleaning corotron~~
- ~~22—photoconductor belt~~
- 15 ~~28, 31 developer unit~~
- ~~29a through 29h,~~
- ~~32a through 32f,~~
- ~~33a, 33b—toner images~~
- ~~33, 34, 35—circulation speeds~~
- 20 ~~40, 57, 61, 68—diagrams~~
- ~~41a, 41b, 42, 43—operating phases~~
- ~~45—paper web~~
- ~~46—dimension of physical page length~~
- ~~47a through 47d—dimension of actual print page length~~
- 25 ~~48a through 48d—print image~~
- ~~55, 65a through~~
- ~~65d—metal plate~~
- ~~56, 60, 67, 71, 80—voltage sources~~
- ~~66a through 66d—switches~~
- 30 ~~70—ground potential of the printer~~
- ~~81—microprocessor~~
- ~~82a, 82b—motor activation unit~~

MARKED-UP COPY

~~83a, 83b — step motors/actuators~~

~~84 — microprocessor~~

~~85 — circulation speed sensor~~

~~86 — desired value provider~~

5 ~~78 — resulting braking force~~

MARKED-UP COPY

Claims

I CLAIM AS MY INVENTION:

MARKED-UP COPY

ABSTRACT OF THE DISCLOSURE

In a method for control of circulation speed of an endless belt arranged in a printer or copier, the endless belt is directed over at least two rollers where the belt is driven with a preset first circulation speed via at least one of the rollers as a driven roller. Various load states act on the endless belt in successive operating phases during a printing or copying process, and via said various load states the belt being braked with different strengths so that a slippage is generated at least between the belt and the driven roller. A braking force acting directly on the endless belt is generated. Braking force is controlled such that a substantially constant slippage is generated between the driven roller and the belt based on the operating phases so that the endless belt is braked to a second circulation speed.

5

10